

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

The Department of Natural Resources is providing this report to satisfy the requirements of the "Procedures Concerning Certain Licenses Act", IC 14-11-4, and its associated administrative rule, 312 IAC 2-3. The application files are available for public inspection at the Division of Water's office in Indianapolis. Please contact the Division's Technical Services Section at (317) 232-4160 or the toll free number 1-877-928-3755 to make an appointment for file review. Photocopies may be made for a nominal charge of \$0.10 per 8 1/2 " X 11" copy.

A pre-action public hearing on an application may be requested by filing a written petition with the Director, Division of Water:

Michael W. Neyer, P.E., Director
Division of Water
Room W264
402 West Washington Street
Indianapolis, Indiana 46204

For a petition to be considered valid it must:

1. Contain the typed or legibly printed name and complete mailing address of each petitioner;
2. Be signed by a minimum of 25 individuals who are at least 18 years old and either reside in the county where the project will take place or own real property within 1 mile of the project site;
3. Affirm that each signatory to the petition satisfies the requirements of item 2; and
4. Identify the application for which the public hearing is being requested either by the application # or the applicant's name and the project description.

A petition which does not meet these requirements will be considered invalid and the hearing request will not be granted.

A person may request that the Department provide written notice of its action on an application by filing a written request with:

Division of Water
Room W264
402 West Washington Street
Indianapolis, Indiana 46204

The request must identify the application by either the application # or the applicant's name and the project description.

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : FW-22686

Stream : Big Lick Creek

Applicant : Mr. Randy Miller
145 East 3rd Street
Marion, IN 46952

Description : The project involves clearing, grubbing, removing blockages and dredging sandbars. Details of the project are contained in information and plans received at the Division of Water on January 8, 2004, and April 1, 2004.

Location : Beginning at ½ mile east of State Road 3 and continuing to County Road 700 East
near Hartford City, Licking Township, Blackford County
SW¼, Section 23, T 23N, R 10E, Pennville Quadrangle
Quad Code: 4008542
UTM Coordinates: Downstream 4476200 North, 639100 East

Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Application # : FW-22744

Stream : McConnel Ditch

Applicant : Thomas Bibakis
17000 Red Oak Drive
Lowell, IN 46356-2087

Description : A new culvert crossing was placed in McConnel Ditch to carry a private drive across the ditch. The new crossing consists of 3, parallel 3' x 20' culverts and 1, parallel 4' x 20' culvert. The culverts aligned with streamflow. Minor channel shaping occurred both downstream and upstream of the crossing to provide a better flow transition into and out of the culvert system. The crown of the roadway over the culverts is at 669.3', NGVD. Details of the project are contained in information and plans received at the Division of Water on February 20, 2004.

Location : Approximately 1600' north of 171st Avenue and 2600' east of Morse Street
near Lowell, Cedar Creek Township, Lake County
SE¼, NE¼, Section 14, T 33N, R 9W, Lowell Quadrangle
Quad Code: 4108734
UTM Coordinates: Downstream 4573310 North, 465589 East

Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : FW-22746

Stream : Yellow Creek

Applicant : Rick Nelson
60810 County Road 13
Goshen, IN 46526-9407

Description : An earthen ditch plug will be constructed across a private ditch to create a 12.7 acre wetland basin. The plug will be approximately 100' long and 3.4' high. It will have a crest approximately 6.6' above the ditch bottom and a 10' top width. The embankment slopes will be 4:1 and 3:1 on the upstream and downstream faces, respectively. The principal spillway will consist of 40' of 15" corrugated metal pipe fitted with 2' x 2' antiseep collars. The principal spillway pipe will be connected to a one way covered riser. The structure is designed to maintain a normal pool approximately 3.6' above the ditch bottom. A riprap covered emergency spillway will be constructed at the west (right) end of the plug. It will have a 10' bottom width, 4:1 sideslopes, and a control set at 4.6' above the ditch bottom. Plans, specifications and color site photographs are enclosed in the application package. Details of the project are contained in information and plans received at the Division of Water on February 23, 2004.

Location : Extending east from County Road 13 approximately 1300' and extending south from Yellow Creek approximately 1400'
near Goshen, Concord Township, Elkhart County
NW¼, SE¼, Section 35, T 37N, R 5E, Foraker Quadrangle
Quad Code: 4108558
UTM Coordinates: Downstream 4607466 North, 589612 East

Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : FW-22768

Stream : St. Joseph River

Applicant : Harold A. and Jean Borneman
1423 Greenleaf Boulevard
Elkhart, IN 46514-3724

Description : A new steel sheet piling seawall will be constructed along 104' of the north bank of the St. Joseph River. The new wall will be attached to an existing steel sheet piling wall on the west and will have a 90 degree corner and wing wall as close as possible to an existing concrete wall on the east end. The new wall will be installed using 12' long X 18" wide interlocking 8 gauge steel piling driven 7.5 ft. into the river bed and anchored by steel sheet deadmen with 1" diameter tie rods at 12' to 15' intervals. Additionally, a full length 2" X 4" X ¼" steel rear facing whaler, a 3" X 5" X ¼" steel top cap and 4" diameter steel drain tubes every 40' will be installed. An existing deteriorating cantilevered pier will be removed and replaced with a 24' X 4' cantilevered walkway parallel to the seawall. Gravel will be placed behind the wall blending to existing grade. Toe protection will be added at the base of the steel sheet piling seawall conforming to the existing bank. Details of the project are contained in plans and information received at the Division of Water on March 3, 2004.

Location : Along the right (north) riverbank, approximately 3500' upstream of the Elkhart Hydro Dam
at Elkhart, Osolo Township, Elkhart County
SE¼, SW¼, SE¼, Section 33, T 38N, R 5E, Elkhart Quadrangle
Quad Code: 4108568
UTM Coordinates: Downstream 4616375 North, 587100 East

Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : FW-22773

Stream : Muddy Fork

Applicant : Americas Window
Bruce Smith
606 East Water Street
Borden, IN 47106-8925

Description : A 40' x 60' storage pole barn has been constructed at grade. Details of the project are contained in information and plans received at the Division of Water on March 4, 2004.

Location : 606 Water Street; along the (left) north bank approximately 700 feet upstream of State Road 60 stream crossing
near Borden, Wood Township, Clark County
NE¼, Section 3, T 1S, R 5E, Borden Quadrangle
Quad Code: 3808548
UTM Coordinates: Downstream 4257625 North, 592485 East

Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : FW-22780

Stream : St. Joseph River

Applicant : Hans and Tina Ashbaugh
1701 Greenleaf Boulevard
Elkhart, IN 46514-3719

Description : An existing deteriorating concrete seawall will be replaced with a steel sheet piling seawall driven immediately streamward of the concrete wall along 180' of the north bank of the St. Joseph River. The new wall will be installed using 10' long x 18" wide interlocking 8 gauge steel piling driven approximately 7' into the river bed and anchored by steel sheet deadmen with 1" diameter steel tie rods at 12' to 15' intervals. Additionally, a full length 2" x 4" x ¼" steel rear facing whaler, a 3" x 5" x ¼" steel top cap and 4" diameter steel drain tubes every 40' will be installed. An existing cantilevered pier will be removed. Approximately 45 cubic yards of gravel will be placed behind the wall topped with a 6" layer of top soil. Details of the project are contained in plans and information received at the Division of Water on March 9, 2004.

Location : Along the right (north) bank, approximately 1 mile upstream from the Elkhart Hydro Project Dam
at Elkhart, Osolo Township, Elkhart County
NW¼, SE¼, SE¼, Section 33, T 38N, R 5E, Elkhart Quadrangle
Quad Code: 4108568
UTM Coordinates: Downstream 4616600 North, 587375 East

Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : FW-22789

Stream : Whitewater River

Applicant : Beige Fields
David Seifferman
214 North Jefferson Avenue
Harrison, OH 45030-1247

Description : An approximately 500' x 1200' area will be excavated approximately 15' to 20' deep along the overbank in the floodway. Most of the fill will be moved outside of the floodway. An approximately 60' wide x 8' high x 1200' long topsoil stock pile will be placed in the floodway. Details of the project are contained in information and plans received at the Division of Water on March 16, 2004.

Location : Along the left (north) overbank, approximately 100' downstream of the confluence with Johnson Fork
near West Harrison, Harrison Township, Dearborn County
NW¼, Section 13, T 7N, R 1W, Harrison, OH-IN Quadrangle
Quad Code: 3908437
UTM Coordinates: Downstream 4349075 North, 686590 East

Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : FW-22798

Stream : West Fork White River

Applicant : Indy Parks and Recreation
Michael Krossschell
200 East Washington Street, Suite 2301
Indianapolis, IN 46204-3387

Description : A stormwater overflow weir will be constructed on the levee along the right (west) bank of the West Fork White River in conjunction with the repair of the existing levee. The levee is being repaired to its original size and elevation. The weir will control outflow from the landward side of the levee to the river and preventing washout and future damage to the levee. The weir will be reinforced concrete 12" thick with a bottom width of 100' at an elevation of 700.5', NGVD which is 0.5' above the 100-year frequency flood elevation of West Fork White River at the site. The ends will have a 2:1 slope to the top of levee elevation of 702.0', NGVD. Sod will be placed landward of the weir and 12" hand placed riprap/stone over geotextile on the river side below the weir down to rock filled gabion baskets at the toe of the levee. Details of the project are contained in information and plans received at the Division of Water on March 23, 2004 and March 26, 2004.

Location : On the right (west) bank of West Fork White River approximately 1500' downstream of the West 30th Street bridge
near Indianapolis, Wayne Township, Marion County
SE¼, NE¼, NE¼, Section 28, T 16N, R 3E, Indianapolis West Quadrangle
Quad Code: 3908672
UTM Coordinates: Downstream 4406350 North, 568600 East

Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : FW-22810

Stream : Tippecanoe River

Applicant : Jason W Ries
2467 North 200 East
Winamac, IN 46996-8679

Description : Construction of a new seawall will be along 100' east side of river, running north\south on bank of the river to deter bank erosion. The new wall will be approximately 4' to 5' high, as measured from the riverbed, will have the same alignment as the neighboring wall, and will tie into existing seawalls located on adjacent properties located to the south. The piling will be driven approximately 4' into the riverbed and will be anchored with deadmen spaced at 2' intervals. 1/4" corrugated steel panels will be placed across the face of the wall to further stabilize the structure. Clean fill will be brought onsite to backfill the area landward of the new seawall. The fill will be leveled with the top of the wall at the river and will be tapered back to existing ground elevations within the project site. Details of the project are contained in information received electronically at the Division of Water on April 1, 2004.

Location : 2467 North 200 East, West Side of House, East Side of River. Seawall to be constructed directly behind house along an approx. 100' of river bank. near Winamac, Monroe Township, Pulaski County

Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : FW-22811

Stream : Unnamed Tributary East
Fork Whitewater River

Applicant : City of Richmond
Richmond Sanitary District
Robert D. Wiwi, P.E.
2380 Liberty Avenue
Richmond, IN 47374-7282

Description : The existing 36" diameter x 113' long culvert carrying Sim Hodgkin Parkway over the unnamed ditch southwest of the Norfolk & Western railroad embankment will be replaced with a new culvert system to reduce upstream flood damages. The new crossing will consist of a 60" diameter x 110' long reinforced concrete pipe culvert having cast in-place concrete headwalls. The new culvert will have an upstream and downstream invert of 895.44 ft, NGVD and 894.89 ft, NGVD respectively. The inlet end of the culvert headwall will be beveled. The culvert and headwalls will be installed in essentially the same location as the existing culvert, skewed approximately 8 degrees compared to the roadway alignment to align with streamflow. Minor channel shaping will occur at both the downstream and upstream inverts of the new culvert to improve the flow transition at the crossing and help prevent future erosion problems. The shaping will be confined to the construction right-of- way. The reshaped areas along the streambank will be stabilized with an 18" thick layer of revetment riprap and the bottom of the channel will be stabilized with a 24" thick layer of Class 2 riprap. The roadway will be replaced to its existing condition, including alignment and grade, upon completion of the required open cut installation. Details of the project are contained in information received electronically at the Division of Water on April 2, 2004.

Location : Approximately 300 feet southwest of the Norfolk & Western railroad overpass of Sim Hodgkin Parkway
at Richmond, Wayne Township, Wayne County
Section 29, T 14N, R 1W, Richmond Quadrangle
Quad Code: 3908478

Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

- Application # : FW-22813
- Stream : West Fork White River
- Applicant : Hamilton County Department of Parks & Recreation
Allen Patterson
15513 South Union Street
Carmel, IN 46033
- Description : A County Park will be developed along the east bank of the West Fork White River. The park will consist of a pedestrian asphalt trail system, canoe launch, and 50 space parking area constructed on asphalt. The pedestrian trail will be placed at grade, not affecting the current topography of the area. However, approximately 300 linear feet of the proposed trail leading to the canoe launch will be sloped at 5%, compared to the existing slope varying from 5% to 33%. The canoe launch will be 4 concrete steps placed within the existing grade, hence not affecting the riverbank. The asphalt parking lot will also be placed at grade for the most part, sloping slightly to allow for positive drainage. The parking lot will be set back 460' from the top of the riverbank and will have a finished elevation of 776.37+/-ft, NGVD. Details of the project are contained in information received electronically at the Division of Water on April 6, 2004.
- Location : The project is located east of Strawtown, IN, which is north of Noblesville in Hamilton County. The site straddles Strawtown Road and encompasses an existing vacant household with the address of 12302 W. Strawtown Avenue. Noblesville. The park acreage is approximately 710 acres.
at Strawtown, White River Township, Hamilton County
- Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : FW-22814

Stream : St. Joseph River

Applicant : Kuhns, PE
55838 Rivershore Est.
Elkhart, IN 46516-1251

Description : An existing railroad tie seawall will be replaced with a new steel sheet seawall along 100' (west) bank of the river to deter bank erosion. The new wall will be approximately 3.5' high, as measured from the riverbed, will have the same alignment as the existing wall, with the exception of a 20' x 22' boat well that will be cut out of the existing bank and will tie into existing seawalls located on adjacent properties located to the north and the south. The piling will be driven approximately 8' -10' into the riverbed and will be anchored with deadmen spaced at 25' intervals. A whaler will be placed across the face of the wall to further stabilize the sheets. Clean fill will be brought onsite to backfill the area landward of the new seawall. The fill will be leveled with the top of the wall at the river and will be tapered back to existing ground elevations within the project site. Details of the project are contained in information received electronically at the Division of Water on April 6, 2004.

Location : 55838 Rivershore Est., Rivershore 2nd addition
near Elkhart, Baugo Township, Elkhart County
Section 11, T 37N, R 4E

Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : FW-22816

Stream : Flat Branch

Applicant : Chris Shilkett
8318 Knapp Road
Indianapolis, IN 46259-9614

Description : A 1300' x 300' area will be filled in the floodplain. The fill will vary in depth from 6" to approximately 5' on the streamward side. The fill's finished elevation will gradually slope from approximately 819.0', NGVD to the existing elevation of the top of the streambank. The fill material was obtained offsite and is already piled in the floodway at the site. Details of the project are contained in information and plans received at the Division of Water on April 5, 2004.

Location : Along the left (north) overbank, beginning at the Knapp Road stream crossing and continuing upstream approximately 1300'
near Beech Grove, Franklin Township, Marion County
SE¼, NE¼, Section 19, T 14N, R 5E, Beech Grove Quadrangle
Quad Code: 3908661
UTM Coordinates: Downstream 4388805 North, 585005 East

Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : FW-22818

Stream : Tiernan Ditch

Applicant : S&J Development
Orrin Sessions
10808 LaCabreah Lane
Fort Wayne, IN 46845-2100

Description : Two areas along the north and south side of the Tiernan Ditch will be excavated for clay and gravel material. The proposed excavation areas will start approximately 700' upstream of Wheelock Road and continue upstream for another 2700'. The proposed excavations will be nominally 5-10' away from the top of bank. The Tiernan Ditch channel will not be excavated or filled during this activity. The north area will have a surface area of approximately 8.2 acres and the south area will have a surface area of approximately 9.8 acres. Both areas will be excavated to a nominal depth of 8 '. The excavated material will be used as "borrow" material for filling building pads in residential subdivisions. The nominal 5-10' strip of undisturbed ground along the Tiernan Ditch and slit fence erected in this area will prevent uncontrolled offsite sedimentation from entering the Tiernan Ditch during this activity. Details of the project are contained in information received electronically at the Division of Water on April 6, 2004.

Location : Along both banks of the Tiernan Ditch starting approximately 600' east of Wheelock Road and continuing upstream for approximately 4000' near Fort Wayne, St. Joseph Township, Allen County
Section 12, T 31N, R 13E, Cedarville Quadrangle
Quad Code: 4108521

Statute/Rule : Flood Control Act, IC 14-28-1, with the associated Flood Hazard Area Rule, 312 IAC 10

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

- Application # : PL-19733
- Lake : Kuhn Lake
- Applicant : James O Britton
26 EMS B 8 Lane
Pierceton, IN 46562-9142
- Description : A concrete seawall will be constructed across 50' of the applicant's frontage. The lakeward face of the wall will be located along the lake's legal shoreline. Details of the project are contained in information and plans received at the Division of Water on February 4, 2004, February 6, 2004 and March 9, 2004.
- Location : 26 EMS B-8 Lane
near Pierceton, Tippecanoe Township, Kosciusko County
SW $\frac{1}{4}$, SW $\frac{1}{4}$, NW $\frac{1}{4}$, Section 26, T 33N, R 7E, North Webster Quadrangle
Quad Code: 4108536
UTM Coordinates: Downstream 4571387 North, 609974 East
- Statute/Rule : Lakes Preservation Act, IC 14-26-2, with the associated Public Freshwater Lake Rule, 312 IAC 11
- Application # : PL-19742
- Lake : Pine Lake
- Applicant : Brian Kempke
723 Waverly
LaPorte, IN 46350-2804
- Description : An existing 40' wide channel along the west shore of Pine Lake will undergo maintenance dredging along 70' of the shoreline to improve navigation and enhance public safety. Approximately 1' of accumulated muck and debris will be removed from the lakebed by dredging to a depth of 5' below the lake's legal level at distance of 40' from the shoreline and uniformly sloping back to the lake's legal level at the shoreline. The excavated material will be transported to an upland containment area for dewatering and disposal. Water from the containment area will not be allowed to return to the lake. Details of the project are contained in information and plans received at the Division of Water on March 1, 2004.
- Location : 723 Waverly Road, Lot 17 and the southeastern 1/2 of Lot 18 in Hall and Rogers Pine Lake Bluff out lots subdivision
near Michigan City, Center Township, LaPorte County
SE $\frac{1}{4}$, SE $\frac{1}{4}$, SE $\frac{1}{4}$, Section 28, T 37N, R 3W, La Porte West Quadrangle
Quad Code: 4108657
UTM Coordinates: Downstream 4607660 North, 520213 East
- Statute/Rule : Lakes Preservation Act, IC 14-26-2, with the associated Public Freshwater Lake Rule, 312 IAC 11

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : PL-19743

Lake : Lake Wawasee

Applicant : Mr. Dan Goller
203 Eunice Drive
South Bend, IN 46615

Description : A concrete seawall will be constructed across 26' of the applicant's frontage. The lakeward face of the wall will be located along the lake's legal shoreline. The deteriorated, existing timber/concrete/rubble seawall will be completely removed. Details of the project are contained in information and plans received at the Division of Water on March 2, 2004, March 9, 2004, and March 19, 2004.

Location : Approximately the south half of the west end of channel between Rosella Street and Sunrise Drive
near Syracuse, Turkey Creek Township, Kosciusko County
NE¼, NW¼, SW¼, Section 14, T 34N, R 7E, Lake Wawasee Quadrangle
Quad Code: 4108546
UTM Coordinates: Downstream 4583828 North, 609498 East

Statute/Rule : Lakes Preservation Act, IC 14-26-2, with the associated Public Freshwater Lake Rule, 312 IAC 11

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

- Application # : PL-19746
- Lake : Lake Wawasee
- Applicant : J Pat and Patricia L Richardson
9778 North Bayshore Drive
Syracuse, IN 46567-7587
- Description : The existing 9' x 23' boatwell will be extended by 3' across the applicant's 41' channel frontage. It will be dredged a maximum depth of 2' below the lake's legal level. The excavated material will be transported to an upland containment area for dewatering and disposal. The existing seawalls along the sides of the boatwell will be removed. A new concrete seawall will be constructed along the sides of the boatwell creating the final 12' x 23' boatwell. In addition, a new concrete seawall will replace the 14.5 existing dilapidated seawalls on each side of the boatwell. The lakeward faces of the walls will be located along the lake's legal normal shoreline. Details of the project are contained in information and plans received at the Division of Water on March 4, 2004.
- Location : 9778 North Bayshore Drive, Lot 24B in the Bayshore Beach Addition
at Syracuse, Turkey Creek Township, Kosciusko County
SW¼, NW¼, NE¼, Section 26, T 34N, R 7E, Lake Wawasee Quadrangle
Quad Code: 4108546
UTM Coordinates: Downstream 4581209 North, 610239 East
- Statute/Rule : Lakes Preservation Act, IC 14-26-2, with the associated Public Freshwater Lake Rule, 312 IAC 11
- Application # : PL-19750
- Lake : Westler Lake
- Applicant : Harold Rea
1275 East 700 South
Wolcottville, IN 46795-9551
- Description : A 10' x 70' underwater beach will be constructed along 35' of the applicant's 70' frontage by placing a uniform 6" layer of pea gravel on the lakebed.
Details of the project are contained in information and plans received at the Division of Water on March 11, 2004 and March 22, 2004.
- Location : 1275 East 700 South
near Wolcottville, Johnson Township, LaGrange County
NW¼, NE¼, NW¼, Section 32, T 36N, R 10E, Oliver Lake Quadrangle
Quad Code: 4108554
UTM Coordinates: Downstream 4599576 North, 633494 East
- Statute/Rule : Lakes Preservation Act, IC 14-26-2, with the associated Public Freshwater Lake Rule, 312 IAC 11

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : PL-19751

Lake : Lake Wawasee

Applicant : Gene Leeuw
510 East Vermont
Indianapolis, IN 46202-3638

Description : A concrete seawall will be refaced with a layer of concrete across 33' of the applicant's 79' frontage. In addition, a concrete seawall will be constructed across 46' of the applicant's frontage. The lakeward face of the wall will be located along the lake's legal shoreline. Details of the project are contained in information and plans received at the Division of Water on March 11, 2004, and March 19, 2004.

Location : 8119 East Sunrise Drive, Lots 59 and 60 in Crous Addition
near Syracuse, Turkey Creek Township, Kosciusko County
NE¼, NW¼, SW¼, Section 14, T 34N, R 7E, Lake Wawasee Quadrangle
Quad Code: 4108546
UTM Coordinates: Downstream 4583858 North, 609503 East

Statute/Rule : Lakes Preservation Act, IC 14-26-2, with the associated Public Freshwater Lake Rule, 312 IAC 11

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : PL-19771

Lake : Pine Lake

Applicant : Mark Kaup
741 Waverly
LaPorte, IN 46350-2804

Description : An existing 40' wide channel along the west shore of Pine Lake will undergo maintenance dredging along 80' of the shoreline to improve navigation and enhance public safety. Approximately 1' of accumulated muck and debris will be removed from the lakebed by dredging to a depth of 5' below the lake's legal level at distance of 40' from the shoreline and uniformly sloping back to the lake's legal level at the shoreline. The excavated material will be transported to an upland containment area for dewatering and disposal. Water from the containment area will not be allowed to return to the lake. Details of the project are contained in information and plans received at the Division of Water on March 1, 2004.

Location : 741 Waverly Road, Lot 19 and the northwestern 1/2 of Lot 18 in Hall and Rogers Pine Lake Bluff out lots subdivision
near Michigan City, Center Township, LaPorte County
SE¼, SE¼, SE¼, Section 28, T 37N, R 3W, La Porte West Quadrangle
Quad Code: 4108657
UTM Coordinates: Downstream 4607660 North, 520213 East

Statute/Rule : Lakes Preservation Act, IC 14-26-2, with the associated Public Freshwater Lake Rule, 312 IAC 11

Indiana Department of Natural Resources / Division of Water

30 Day Public Notice Report

Application # : PL-19773

Lake : Lake George

Applicant : City of Hobart
Mayor Linda Buzinec
414 Main Street
Hobart, IN 46342-4444

Description : Replace 180' of collapsed seawall along the applicant's 800+ linear feet of shoreline on the west side of the northern section of Lake George in the City of Hobart, Indiana. The new wall will be reinforced, poured concrete which will be sloped on the water side, with a height of 36" and will vary uniformly in thickness from 8" to 12" from the base to the top. at least 24" of 3" rip rap shall be placed on the water side of the wall at the base. Details of the project are contained in information received electronically at the Division of Water on May 2, 2004.

Location : The project is located on the west shore of the northern section of Lake George at Hobart, Hobart Township, Lake County

Statute/Rule : Lakes Preservation Act, IC 14-26-2, with the associated Public Freshwater Lake Rule, 312 IAC 11